



SCHEMA TECNICA TECHNICAL DATA SHEET

ST. 04A.0060._G00.

Rev. 04

Pag. 1/1

Date

14.10.14

FILTRI PER ARIA COMPRESSA COMPRESSED AIR FILTERS

MODEL	MODELLO	F 0010		
RATED FLOW:	PORTATA :	l/min	1170	
		mc/h	70	
		SCFM	41	
Working press.	Pressione Nom.	bar	7	(Max. 16)
Air connections	Attacchi	IN/OUT	1/2" G	
Weight	Peso	kg	0,6	
Dimensions	Dimensioni	A	mm	220
		B	mm	90
		C	mm	25

Accessories

Accessori

Pressure drop indicator	On request	Indicatore intasamento	A richiesta
Automatic drain discharger	On request	Scaricatore autom.	A richiesta

Filter type	Tipo filtro	STD	DF	QF	PF	HF	CF
Complete filter Code	Codice filtro completo		04A.0060.DG	04A.0060.QG	04A.0060.PG	04A.0060.HG	04A.0060.CG
Filter elements code	Codici elem. ricambio		04E.0060.D	04E.0060.Q	04E.0060.P	04E.0060.H	04E.0060.C
Physical filtration process			Interception	Interception	Interception +coalescing	Interception +coalescing	Adsorption
Principio fisico di filtrazione			Intercettazione	Intercettazione	Intercettazione +coalescenza	Intercettazione +coalescenza	Adsorbimento
Max. solid dimension intercepted	Massimo trattenimento partic. Solido	ISO 8573-1/01 μm	10	5	1	0,01	//
Remaining oil content after filtration	Residuo oleoso dopo la filtrazione	ISO 8573-1/01 mg/m^3	//	//	0,1	0,01	0,003
Max. inlet air temperature	Max. temperatura ingresso aria	$^{\circ}\text{C}$	100	100	100	100	60
Press. Drop with new filter elements	Perdita di carico nuovi elementi.	bar	0,07	0,05	0,1	0,1	0,08
Press. Drop with saturated filter el.	Perdita di carico elementi saturi	bar	0,6	0,6	0,6	0,6	0,6
Element replac. Time	Sostituzione elemento saturo.	h	4000	4000	3500	3500	3000

